

## Phoenix FireBird Compact 50Hz Electric Heat Drying System

### Powerful, Portable and Safe Heat

Phoenix has added another HOT option to its electric heat product offering. Powerful, Portable and Safe BTUs exactly where you need them – the FireBird Compact 50 Hz can provide up to 3,960W (13,503 BTUs) of instant heat and, with its 33cm x 32cm x 66cm (13" x 12.5" x 26") durable stainless steel cabinet, can operate virtually anywhere on the job site that heat is needed to speed up the drying process.

The FireBird Compact portable electric heater features dual power receptacles for connection to common 240VAC outlets. The Compact can output up to 3,960W (13,503 BTUs) of clean, safe heat at 425M3/hr (250 CFM). The Compact's remote thermostat, included with the unit, provides a means to control the temperature in the drying chamber, while its internal temperature cutout ensures safe operation.

At maximum heat (2-8.5 Amp Circuits @ 1920W & 2040W), the FireBird produces 3,960W (13,503 BTUs) – that provides 425M3/hr with a 28°C temperature rise. Internal thermal controls monitor inlet air temperature to prevent overheating an area. To ensure external surfaces are safe to touch, the heating elements are shielded within a double-walled and screened enclosure.

The FireBird Compact offers multiple heating, ducting, and electrical options for on-demand heating from inside or outside the drying space. The FireBird Compact will operate freestanding or with 8-inch flex duct on the inlet (optional) and 8-inch outlet to distribute the heat precisely where you need it.

The Phoenix FireBird has combined the safety, security, and convenience of electric heat with the legendary reliability of our proven restoration equipment. The FireBird Compact is a compact, powerful drying tool – just another example of Phoenix Restoration Equipment giving the restoration professional the right tool in the right size for any restoration job.



### Features

- Compact Size, Lightweight
- Double-Walled, Screened Enclosure for heating elements
- Automatic Internal 60°C (140°F) Safety Thermal Cutout
- Phoenix Thermostat with 7.62m (25') connecting wire included with the unit
- Stainless steel cabinet
- Stackable for easy storage and transportation



Stack up to 6 units with a strap for storage and transportation



MADISON, WISCONSIN

[www.UsePhoenix.com](http://www.UsePhoenix.com)

[www.FaceBook.com/UsePhoenix](http://www.FaceBook.com/UsePhoenix)

[www.YouTube.com/user/Use Phoenix](http://www.YouTube.com/user/UsePhoenix)

Let's Be Friends



View Our Videos



Connect with Us



## Phoenix FireBird Compact

### Specifications

- Part No.** 4036560-00
- Power** 240VAC 50Hz, 1 Phase Heater Circuits (up to 2):  
 1st 8.5 Amp / 1,920W (6,547 BTU) Temperature Rise = 14° C (25° F)  
 2nd 8.5 Amp / 2,040W (6,956 BTU) Temperature Rise = 14° C (25° F)  
 At Maximum Heat: 3960W (13,503 BTU) Temperature Rise = 28° C (50° F)
- Blower** 425m<sup>3</sup>/hr (250CFM)
- Filters** Mini Pleated Media MERV-11
- Duct Options** Intake - 8" Flex-Duct (Optional)  
 Supply - 8" Flex-Duct
- Warranty** One year 100% of Parts and Labor

### Dimensions

	Machine	Shipping
Width	33cm (13")	43cm (17")
Height	32cm (12.5")	43cm (17")
Depth	66cm (26")	76cm (30")
Weight	16kg (35 lb)	19kg (42 lb)

### Popular Accessories And Replacement Filters

- 4033895 Duct Kit, Compact Heater, 8" inlet (no flex Duct)
- 4027415 8" x 25' Flex Duct
- 4030671 9" x 11 3/8 x 3/4" Mini-Pleated MERV-11 Filter
- 4030733 Filter Package, 12 PK; 9" x 11 3/8 x 3/4" Mini-Pleated MERV-11 Filter
- 4030115 Reed LM 8000 Multi-Function Meter
- 4027327 Phoenix Remote Thermostat Kit



Included remote thermostat




2-8.5 amp circuits Up to 3,960W (13,503 BTUs)



Ductable 8" outlet



Mini Pleated MERV-11 filter



Optional 8" inlet duct adapter